| 1   | 10A NCAC 41I  | 3 .0503 is proposed for amendment as follows:   |
|-----|---|---|
| 2   |   |   |
| 3   | 10A NCAC 41   |   |
| 4   | · /   | ng breath alcohol screening test devices are approved as to type and make:                            |
| 5   | (1)   | ALCO-SENSOR (with two-digit display), <u>manufactured</u> made by Intoximeters, Inc.                  |
| 6   | (2)   | ALCO-SENSOR III (with three-digit display), <u>manufactured</u> made by Intoximeters, Inc.            |
| 7   | (3)   | ALCO-SENSOR IV, manufactured by Intoximeters, Inc.  |
| 8   | (4)   | ALCO-SENSOR FST, manufactured by Intoximeters, Inc.   |
| 9   | (5)   | S-D2, manufactured by CMI, Inc.   |
| 10  | (6)   | S-D5, manufactured by CMI, Inc.   |
| 11  | <u>(7)</u>  | ALCO-SENSOR III (Enhanced with Serial Numbers above 1,200,000), manufactured by                       |
| 12  |   | Intoximeters, Inc.  |
| 13  | (8)   | ALCO-SENSOR FST (Enhanced with Serial Numbers 200,000 and higher), manufactured by                    |
| 14  |   | Intoximeters, Inc.  |
| 15  | <u>(9)</u>  | LIFELOC FC10, manufactured by Lifeloc Technologies, Inc.  |
| 16  | <u>(10)</u>   | INTOXILYZER 500, manufactured by CMI, Inc.  |
| 17  | <u>(11)</u>   | ALCOVISOR MERCURY, manufactured by PAS International.   |
| 18  | (b) The agency or operator shall verify instrument calibration of each alcohol screening test device at least once during |   |
| 19  | each 30 day per   | iod of use. The verification shall be performed using by employment of an alcoholic breath simulator  |
| 20  | with a using simulator solution in accordance with Paragraph (c) of this Rule the rules in this Section or an ethano      |   |
| 21  | gas canister in a   | accordance with Paragraph (d) of this Rule. eanister.   |
| 22  | (c) Alcoholic l   | preath simulators used exclusively to verify instrument calibration of alcohol screening test devices |
| 23  | shall have the solution changed every 30 days or after 25 calibration tests, whichever occurs first.                      |   |
| 24  | (d) Ethanol gas canisters used exclusively to verify instrument calibration of alcohol screening test devices shall not   |   |
| 25  | be utilized beyo  | and the expiration date on the canister.  |
| 26  | (e) Requirements of Paragraphs (b), (c), and (d) of this Rule shall be recorded on an alcoholic breath simulator log or   |   |
| 27  | an ethanol gas canister log designed by the Forensic Tests for Alcohol Branch within the North Carolina Department        |   |
| 28  | of Health and Human Services and maintained by the user agency in accordance with the user agency's retention             |   |
| 29  | policy. agency.   |   |
| 30  | <del></del>   |   |
| 31  | History Note:   | Authority G.S. 20-16.3;   |
| 32  |   | Eff. February 1, 1976;  |
| 33  |   | Readopted Eff. December 5, 1977;  |
| 34  |   | Amended Eff. July 1, 2007; November 1, 2005; April 1, 2001; January 1, 1995; January 4, 1994;         |
| 35  |   | April 1, 1993; January 4, 1993;   |
| 36  |   | Pursuant to G.S. 150B-21.3A, rule is necessary without substantive public interest Eff. January 9,    |
| 37  |   | 2018.   |
| J 1 |   | #V1V.   |